

HOLDER

PERFORMANCE MEETS EFFICIENCY

HOLDER C 55 IN PERFECTED COMBINATION WITH THE GMR TRIPLEXMOWER





TECHNICAL DATA

	C 55 SC		GMR TRIPLEX
ENGINE	Kubota 4-cylinder, 4-stroke diesel	WORKING WIDTH	From 2,50 m
Power	42 kW (57 HP)	CUTTING	5 Mulching knifes
Fuel tank capacity	65 I		
DRIVE	Hydrostatic drive, digital control, continuously adjustable travel speed regulation, sprung front and rear axles. Permanent all-wheel drive across four equal sized wheels.	DRIVE	Central deck PTO driven, hydraulic driven wings
Differential lock	Front and rear mechanical, electro-hydraulically switchable at the same time, applied 100% to both axles	MAINTENANCE OPTIONS	Tiltup-function, lubrication service points
Speed	40 km/h		
PTO shafts	Powershift independent PTO shafts at the front, can be switched separately mechanically driven, 1000 rpm	SECURITY FEATURES	Automatic shut down of the wings from a lift of 30°
HYDRAULICS	35 l/min hydraulic pump, with the option to add an additional 80 l/min adjustable pump		





YOUR TOP ADVANTAGES

- Silent working mode with low fuel consumption with only 1900 rpm
- Closer mounted mowing deck allows a great overall view and lower turning radius
- Less manual work needed due to singular deck lifting
- Floating position allows perfect copying of the ground and low ground pressure
- Multifunction of a Holder as usual





