

**HOLDER
B/C SERIES**



B 55 SC



C 55 SC



C 65 SC / TC



C 70 SC / TC

	1-person-cab		1- / 2-person-cab	
ENGINE	Kubota 4-cylinder-4-stroke diesel		Kubota 4-cylinder-4-stroke turbo diesel	
Emission standard	Stage 5			
Power	42 kW (57 HP)		48 kW (65 HP)	
Displacement	2615 cm ³			
Torque	167,5 Nm		225,0 Nm	
Rated speed	2700 rpm		2400 rpm	
Cooling system	Water cooling			
Fuel tank capacity	65 l			
DRIVE	Hydrostatic traction drive, controlled digital-electrically, stepless road speed control			
	Permanent four-wheel drive via four wheels of the same size		PowerDrive via four wheels of the same size	
Speed	0 – 40 km/h			
Differential lock	Mechanical at the front and rear, simultaneously switchable electrohydraulically, acts on both axles at 100 %			
Brakes	Hydraulically actuated drum brake on the front axle, acts on all four wheels as four-wheel brake via the hydrostatic traction drive, electrically actuated stop brake on the front axle		Hydraulically actuated four-wheel brake, electrically actuated stop brake on the front axle	
PTO shafts	Front: - Rear: hydraulically powered, 540 rpm, Size: 1 3/8 inch	Optional: power-switchable, independent PTO shaft, can be switched separately at the front and rear, front: mechanically powered, 1000 rpm or optionally 540 rpm Rear: hydraulically powered, 540 rpm, Size: 1 3/8 inch		
HYDRAULICS	Hydraulic pump 35 l/min optionally extendable with additional device variable displacement pump 80 l/min		Hydraulic pump 35 l/min optionally extendable with additional device variable displacement pump 70 l/min	
Quantity of hydraulic oil	37 l		37 l	
Lifting force	Front 1100 kg / rear 1100 kg			
Three-point lift	Standard three-point, arrester hook steplessly adjustable from CAT IN to CAT I			
Additional control valves	High expandability, adapted for the purpose			
WEIGHTS	Including driver at 75 kg, depending on tyres and equipment			
Empty weight	1928–2445 kg		SC: 1928 – 2445 kg TC: 2089 – 2603 kg	
Permissible total weight	3500 kg		3500 – 3800 kg	3500 – 4000 kg
Permissible axle load	Front 2300 kg / rear 2300 kg			
Tow bar load on the trailer coupling	Max. 600 kg			
Towing capacity	Unbraked 1500 kg / overrun braked 3500 kg			
Maximum payload (40 km/h)	1572 kg		SC: 1872 kg TC: 1711 kg	
DIMENSIONS	Depending on tyres and cab mounting			
Wheelbase	1820 mm		SC: 1820 mm TC: 1870 mm	
Total length	2928–3770 mm		SC: 2928 – 3770 mm TC: 3301 – 4190 mm	
Total height	1985 mm	2010–2260 mm	SC: 2010 – 2260 mm TC: 2220 – 2272 mm	SC: 2050 – 2260 mm TC: 2220 – 2272 mm
Total outer width	1170–1530 mm		SC: 1170 – 1530 mm TC: 1360 – 1530 mm	
Turning circle radius	1170–1530 mm		SC: From 1490 mm TC: From 1620 mm	
Inner flatbed dimensions	1250 x 1060 x 300 mm or 1330 x 1260 x 300 mm			