



Vredo Overseeders

DZ SUPERcompact



High standards required....

The traffic at your golf course is very high. Which is why it is necessary that you provide your greens and tees regularly, and in a short period of time, with new grass seed. The course needs to stay at a high quality, so the greens need to be in optimum condition after maintenance. You want the grass seed and the seedlings to be clamped in the soil, so they don't get mowed and play can resume on schedule. Sport fields share similar demands with time constraints during summer breaks, and need to be worked on quickly and efficiently. Because of the sowing distance of 3.5 cm you cover a lot of ground in one pass. The machine needs to be delicate but solid, with a high capacity and easily transportable.

.....Perfection delivered

The SUPERcompact meets all these requirements. On greens this machine can seed fine seed like Agrostis (Bent grass) in very precise amounts (>3 gr/m²) and depths (3/4 mm). But on the other hand, the dosing can be set on 300 kg English Rye per hectare, to overseed a sports field. The machine is available in a towed and a three point version. The sowing depth is adjustable from 0 to 20 mm without steps. The towed version will keep the correct sowing

depth, even on extremely undulating grounds. The three point version is extremely maneuverable and is built very compact to save space on the trailer, which makes the road transport very efficient.

Unique features

The seed dosage of the Vredo SUPERcompact is variable, so there is never too much or too little seed being dispersed. You determine the amount of seed, with the help of the practical spindle and seed chart, which shows the most common types of grass and mixtures. The seed is regulated through the cam wheel and the bottom flap, from the beginning until the end in all its movements. The sharp discs, with a diameter of 250 mm, also provide surface aeration and the roller ensures a smooth and fast green. Because all soil conditions and environmental factors like wind and sun are unique, every surface requires its own specific adjustment. With the Vredo SUPERcompact this is child's play. By using the calibration tray and the extensive seed chart, the dosing is exact and very easily adjustable. This robust machine has been built using high quality materials, which makes it an investment for life.



VREDO double disc system

Vredo SUPERcompact; "Build with care to play like a pro!"



The best in the field



Standard new features

- A Spindle**
To quickly adjust the quantity of seed. With use of the seed chart at the inner side of the lid, this is an easy job.
- B Gas cylinder**
To open and close the lid smoothly after filling the seed tank.
- C LED lights**
Bright light with clear direction signs and brakes for transport on the road.

Options

- 1 Weight frame with weight carrier**
To make sure the discs have an optimal result on every desired depth, extra weight is necessary. So a weight carrier is recommended.
- 2 20 kg weight**
Easily mountable weights, provided with a handle to put on extra weight on the machine, they fit the weight carrier, for optimal results of the machine.
- 3 Hydraulic brake system**
The hydraulic brake system is a must for extra road safety.
- 4 Tow bar with electric plug (towed option)**
To hook up extra trailers with material or grass seed. Efficiency in logistics!
- 5 Ball coupling**
For safe shockproof road transport with maximum movability between the machine and tractor

Specifications **Vredo DZ SUPERcompact**

Seed distribution	Disc diameter	Element	Turf guard	Size tires	Calibrate
Variable 3 till 390 kg/a	Ø 250 mm	Progressive suspension 0-20mm sowing depth	Adjustable	260/12 R12 lawn profile	Calibrate chart, calibrating trays

Model	Working width	Row distance	Contents seed hopper	Compaction roller	Dimensions	Weight ex	Max. recommended weights	Total weight incl. frame/carrier	Required Tractor Power
3 Point									
DZ208.035	0,80 m.	3.5 cm	80 l.	80 l.	1,35 x 1,02 x 1,1 m.	510 kg.	8 (20 kg per weight)	720 kg	30 pk/hp
DZ212.035	1,22 m.	3.5 cm	120 l.	120 l.	1,35 x 1,42 x 1,1 m.	660 kg.	12 (20 kg per weight)	970 kg	45 pk/hp
DZ216.035	1,57 m.	3.5 cm	160 l.	160 l.	1,35 x 1,82 x 1,1 m.	810 kg.	16 (20 kg per weight)	1220 kg	55 pk/hp
DZ218.035	1,78 m.	3.5 cm	180 l.	180 l.	1,35 x 2,02 x 1,1 m.	890 kg.	18 (20 kg per weight)	1300 kg	75 pk/hp
DZ222.035	2,13 m.	3.5 cm	220 l.	220 l.	1,35 x 2,42 x 1,1 m.	1050 kg.	22 (20 kg per weight)	1600 kg	85 pk/hp
Towed									
DZ212.035T	1,22 m.	3.5 cm	120 l.	120 l.	3,2 x 1,42 x 1,1 m.*	980 kg.	10 (20 kg per weight)	1250 kg	30 pk/hp
DZ216.035T	1,57 m.	3.5 cm	160 l.	160 l.	3,2 x 1,82 x 1,1 m.*	1130 kg.	14 (20 kg per weight)	1500 kg	45 pk/hp
DZ218.035T	1,78 m.	3.5 cm	180 l.	180 l.	3,2 x 2,02 x 1,1 m.*	1210 kg.	16 (20 kg per weight)	1580 kg	55 pk/hp
DZ222.035T	2,13 m.	3.5 cm	220 l.	220 l.	3,2 x 2,42 x 1,1 m.*	1370 kg.	20 (20 kg per weight)	1880 kg	65 pk/hp

* The tow bar can be easily taken apart, due to this the length is only 2.2 meters instead of 3.2 meters.
The compaction roller can be filled, for extra weight.

www.vredo.com
+31 (0) 488 411 254
sales@vredo.com

Copyright © 2016 Vredo Dodewaard BV. All rights reserved.
All product information was correct at time of printing.

Dealer:

Vredo

The best in the field