For Earth, For Life Kubota



KUBOTA Z2-481 ZERO-TURN MOWER

The residential mower that performs like a professional





First of all residential

For private large garden owners Z2-481 guarantees general cutting without delay or time consumption around trees and other obstacles within a large grassed area. 4 the main reasons why Z2-481 is the correct choice:

- 360° turning technology: lets you mow around obstacles with incredible ease, making every mowing manoeuvre more efficient.
- Unsurpassed comfort: K-ride deluxe fully adjustable seat with suspension adjustment. Anti-vibration floor plate and drive levers.
- Quick, easy deck adjustment: Once the cutting height is set, simple pedal operated raise/lower of the cutting deck.
- Full protection: ROPS frame which can be folded down. Seat belt. Rear bumper bar to prevent damage to the rear and engine compartment.







Safety first

ROPS protection and seat belt ensures operator safety when working on inclines. The ROPS is foldable allowing the machine to be stored in a low entrance building or when cutting under low branches.



All major operating controls grouped together

The console is contoured to allow the controls to be at the correct angle for ease of use.



Rear end protection

A rear bumper bar protects the area from accidental damage. A rear trailer towing pin expands the machine's versatility.



Outstanding comfort

A fully adjustable deluxe seat. Deep padded seat and backrest, armrests, padded grip drive levers and a spacious platform floor area makes the Z2-481 a truly pleasurable experience.

6 Z2-481 ———

#Complete package

Deck operation simply the best



K-Lift. Deck raise/lower control

Foot operated pedal allows the operator to raise the deck if required. Releasing the pedal will return the deck to the selected cutting height every time. The angle of the pedal ensures comfortable operation.



Quick dial deck height adjustment

Simply turning the dial adjusts the cutting height by ¼" (6 mm) increments. For transportation set the dial in the highest position.



Anti-vibration dampers

The floor plate is not only removable allowing access to the deck drive belts but is also mounted on rubber dampers which removes any vibration that might be felt through the floor. The drive levers are also anti-vibration to remove any discomfort felt through your hands.



#Performance

Power equates to performance.

You need the power to achieve the performance.



V Twin petrol engine

Powered by Kawasaki. The design of V twin engines allows them to run quieter and smoother with less vibrations than traditional single cylinder engines.



Easy access encourages regular checks

A lift-up flap exposes the air filter which can be quickly removed and cleaned. The engine oil dipstick is incorporated into the filler cap and can be effortlessly removed and checked.



Push button start

A key fob allows easy one-handed operation of the choke and engine start switch.





Excellent weight distribution Low profile tyres ensure no damage or compaction of the turf. Stylish wheel rims add to the sleek look of the Z2.481.

Transmission drive and turning within your grasp

Ultimately zero turn mowers are bought for their unique ability to turn with zero turning radius. The drive motion levers operate two independent hydrostatic units which control the drive wheels. The anti-vibration levers with comfortable grip pads provides the operator with complete control.

10 Z2-481 ———





48" / 1220mm side discharge deck

Side discharge is particularly effective in longer, dense, or moist grass as there is limited build-up on the underside of the mowing deck.



Off-set front wheels

Front wheels are slightly offset to ensures optimum grass cut. The grass folded by the wheels is on the way of the blade coming to raise up the grass.



Mulching kit available

A mulching kit can be fitted to the standard deck which cuts and feeds the chopped grass back into the turf.

Welded steel construction

High strength welded steel deck offers the durability required for these operations.



Cutting blade operation

The design of the blades and contour of the cutting chamber not only enhances the cutting quality, but also the airflow to provide a fast and effective grass discharge.

72-481 ———

#Let's summarize

The Kubota Z2-481 residential mower that performs like a professional.

And here's why.





Ultimate comfort

Deluxe deep padded, fully adjustable seat. K-Ride with adjustable suspension, anti-vibration floor plate and drive levers.



Transmission drive with comfort and

The drive levers are not only comfortable to operate, but they are also responsive to the operational requirements. Superb reaction to obstacle manoeuvres.




Deck adjustment and operation

K-Lift foot control lever allows quick and easy lifting/lowering of the deck. Cutting height dial adjustment at the operator's



Robust deck construction and fine cut finish

High strength welded steel deck. The shape of the cutting chamber together with the durable cutting blades ensure a high quality cut.



V-Twin air-cooled petrol engine not only produces the power back-up required, but the design enhances the fuel



2-years / 300 hours warranty

Kubota stands by its statement of providing high quality, reliable produces with one of the best warranty periods on

#Technical data





Model	Z2 .481
Engine	V3800-CR-TIE5
Manufacturer	Kawasaki
Model	FR651V
Emissions Stage	5
Cylinder n°	90° V-twin
Displacement cc	726
Fuel system	Unleaded petrol
Ignition system	Electronic spark ignition
Cooling system	Air
Gross power (SAE J1995) Hp/kW	21.5 / 16.0
Engine speed (Rated) rpm	3600
Engine hand accelerator	•
Fuel tank capacity litres	16
Fuel gauge	Sight Window type
Transmission	
Transmission type	Hydrostatic Transmission
Forward speed range km/h	0 – 12.9
Reverse speed range km/h	0 – 6.3
Operator platform	
Seat	21» Deluxe High Back Seat w/ armrests w/ 1.5» stroke suspension
Hour meter	•
Foldable ROPS	•
Drinks holder	•
Storage box	•
Towing hitch	•
Mower deck	
Deck lifting / lower	Mechanical Foot Lift Pedal
Deck mounting	Quick connect, parallel linkage
Discharge direction	Side
Cutting width mm	1219 (48»)
No. of blades	3
Cutting height range mm	38 – 114 (1.5" – 4.5")
Cutting height increments mm	6 (0.25")
Adjustment of Cutting Height	Dial adjustment system
Anti-scalp rollers	Fixed
Brakes and steering	
Parking brake	•
Parking brake engagement	Console lever
Steering and driving operation	2 hand levers with height and angle adjustment
РТО	
PTO drive system	Belt
Drive clutch type	Electro-magnetic
Dimensions and weights	
Front tyres	13x6.5-6 Smooth, semi-pneumatic
Rear tyres	22x10.0-14 Turf, low profile
	1195
Wheelbase (A) mm	1130
Wheelbase (A) mm Overall length (B) mm	2006
Overall length (B) mm	2006
Overall length (B) mm Overall height (With ROPS upright) (C) mm	2006 1738
Overall length (B) mm Overall height (With ROPS upright) (C) mm Overall height (With ROPS folded) mm Overall Width (Without mower deck) (D) mm Overall Width (With mower deck - side	2006 1738 1240 1207
Overall length (B) mm Overall height (With ROPS upright) (C) mm Overall height (With ROPS folded) mm Overall Width (Without mower deck) (D) mm Overall Width (With mower deck - side discharge) (E) mm	2006 1738 1240 1207 1552
Overall length (B) mm Overall height (With ROPS upright) (C) mm Overall height (With ROPS folded) mm Overall Width (Without mower deck) (D) mm Overall Width (With mower deck - side discharge) (E)	2006 1738 1240 1207

14 15 Z2-481 ———

Kubota (U.K.) Limited

Dormer Road Thame, Oxfordshire, OX9 3UN

http://www.kubota.co.uk

This publication may not be reproduced in whole or in part in any form without the prior written consent of KUBOTA. It corresponds to the status at the time of going to press. The manufacturer reserves the right to change technical specifications without notice. Some of the parts shown in the publication are optional and are not part of the standard equipment. Information on warranty and safety as well as further product information can be obtained from the responsible KUBOTA authorized dealer.

